

TECHNICAL REPORT

SUNBLOCK



M2/B1/BS

APPLICATIONS

- Marquee roofing fabric
- Small structures

PRODUCT INFORMATION

WIDTH	250 or 300 cm
WEIGHT	850 g/m ²
BASE CLOTH	high tenacity polyester 1100 dTex
COATING	PVC coating, system LOWICK [®] Protection Anti UV
FINISH	CLEANGARD [®] lacquer both sides
COLOUR	Lacquered : white, beige, grey Grain textile finish : white, beige, grey 3D finish : White, beige

PRODUCT CHARACTERISTICS

TENSILE STRENGTH	260/ 250 daN	NF EN ISO 1421
TEAR STRENGTH	32/28 daN	DIN 53363
ADHESION	8 daN / 5 cm	NF EN ISO 2411
TRANSLUCENCE	0 %	XP T 54 199
TEMPERATURE STABILITY:		
in ° Celsius	- 30°C to + 70°C	
in ° Fahrenheit	- 22°F to +158°F	
F / R	M2/B1/BS NFPA 701 / B-s2-d0	

Average values +/- 10 % non contractual



415 avenue de Savoie – SAINT-CLAIR-DE-LA-TOUR – 38357 La Tour du Pin
FRANCE

Tél. 33 (0)4 74 83 51 00 – Fax 33 (0)4 74 83 51 01

www.dickson-coatings.com